



P14034386

USA



INVESTOR IN PEOPLE

CERTIFIED COPY OF PRIORITY DOCUMENT

The Patent Office
Concept House
Cardiff Road
Newport
South Wales
NP10 8QQ



I, the undersigned, being an officer duly authorised in accordance with Section 74(1) and (4) of the Deregulation & Contracting Out Act 1994, to sign and issue certificates on behalf of the Comptroller-General, hereby certify that annexed hereto is a true copy of the documents as originally filed in connection with the patent application identified therein.

In accordance with the Patents (Companies Re-registration) Rules 1982, if a company named in this certificate and any accompanying documents has re-registered under the Companies Act 1980 with the same name as that with which it was registered immediately before re-registration save for the substitution as, or inclusion as, the last part of the name of the words "public limited company" or their equivalents in Welsh, references to the name of the company in this certificate and any accompanying documents shall be treated as references to the name with which it is so re-registered.

In accordance with the rules, the words "public limited company" may be replaced by p.l.c., plc, P.L.C. or PLC.


Re-registration under the Companies Act does not constitute a new legal entity but merely subjects the company to certain additional company law rules.

Signed

AEvens.

Dated

28th March 2000



THIS PAGE BLANK (USPTO)

Request for grant of a patent
(See notes on the back of this form. You can also get an explanatory leaflet from the Patent Office to help you fill in this form)

02 SEP 1999

The Patent Office

Cardiff Road
Newport
Gwent NP9 1RH

1. Your reference	PHB 34386		
2. Patent application number (The Patent Office will fill in this part)	9920615.3		
3. Full name, address and postcode of the or of each applicant (underline all surnames)	KONINKLIJKE PHILIPS ELECTRONICS N.V. GROENEWOUDSEWEG 1 5621 BA EINDHOVEN THE NETHERLANDS		
Patents ADP Number (if you know it)	7419294001		
If the applicant is a corporate body, give the country/state of its incorporation	THE NETHERLANDS		
4. Title of the invention	BATTERY ECONOMISING IN A COMMUNICATIONS SYSTEM		
5. Name of your agent (if you have one)	COLIN JAMES MOODY		
"Address for service" in the United Kingdom to which all correspondence should be sent (including the postcode)	Philips Corporate Intellectual Property Cross Oak Lane Redhill Surrey RH1 5HA		
Patents ADP number (if you know it)	7652263001		
6. If you are declaring priority from one or more earlier patent applications, give the country and the date of filing of the or of each of these earlier applications and (if you know it) the or each application number	Country	Priority Application number	Date of filing
7. If this application is divided or otherwise derived from an earlier UK application, give the number and the filing date of the earlier application	Number of earlier application	Date of filing (day/month/year)	
8. Is a statement of inventorship and of right to grant of a patent required in support of this request? (Answer "Yes" if:	YES		
a) any applicant named in part 3 is not an inventor, or			
b) there is an inventor who is not named as an applicant, or			
c) any named applicant is a corporate body.			
See note (d))			

Patents Form 1/77

9. Enter the number of sheets for any of the following items you are filing with this form.
Do not count copies of the same document.

Continuation sheets of this form

Description	8x2
Claims(s)	2x2
Abstract	1x2
Drawings	4x2

10. If you are also filing any of the following, state how many against each item:

Priority Documents

Translations of priority documents
Statement of inventorship and right
to grant of a patent (*Patents Form 7/77*)
Request for preliminary examination and
search (*Patents Form 9/77*)
Request for substantive examination

(*Patents Form 10/77*)
Any other documents

(Please specify)

11. I/We request the grant of a patent on the basis of this application.

Signature

Date

1st September 1999

12. Name and daytime telephone number of person to contact in the United Kingdom

01293 81 5278

C J MOODY

Warning

After an application for a patent has been filed, the Comptroller of the Patent Office will consider whether publication or communication of the invention should be prohibited or restricted under Section 22 of the Patents Act 1977. You will be informed if it is necessary to prohibit or restrict your invention in this way. Furthermore, if you live in the United Kingdom, Section 23 of the Patents Act 1977 stops you from applying for a patent abroad without first getting written permission from the Patent Office unless an application has been filed at least 6 weeks beforehand in the United Kingdom for a patent for the same invention and either no direction prohibiting publication or communication has been given, or any such direction has been revoked.

Notes

- If you need help to fill in this form or you have any questions, please contact the Patent Office on 0645 500505.
- Write your answers in capital letters using black ink or you may type them.
- If there is not enough space for all the relevant details on any part of this form, please continue on a separate sheet of paper and write "see continuation sheet" in the relevant part(s). Any continuation sheet should be attached to this form.
- If you have answered "Yes" *Patents Form 7/77* will need to be filed.
- Once you have filled in the form you must remember to sign and date it.
- For details of the fee and ways to pay please contact the Patent Office.

DESCRIPTION

BATTERY ECONOMISING IN A COMMUNICATIONS SYSTEM

5 The present invention relates to a method of battery economising in a communications system, to a communications system and to a receiving station for use in the system. The communications system may comprise a telecommunications system such as a paging or cordless/cellular telephone system or telemetry system for example an automatic meter reading system.

10

 In many telecommunications and telemetry applications, equipments are on standby for extended periods of times, for example months if not years. Consequently for battery powered equipments, any means of extending the useful life of a battery power source is of importance. For radio equipments
15 the receiver is often the dominant source of power consumption within the equipment.

 Power saving in receivers of radio equipments has been practised for a relatively long time in for example the digital paging field. The POCSAG
Paging Standard or CCIR Radiopaging Code No. 1 has an inherent power
20 saving capability because under the protocol time is divided into successive time periods called batches. A batch comprises a sync code word and 8 frames. A receiver is powered for receipt of a sync code word and for a predesignated one of eight frames in successive batches, any messages for the receiver being transmitted in the predesignated frame. During the time
25 periods between the sync code word and the predesignated frame and vice versa, the receiver can be powered down.

 EP-B1-0 554 941 discloses the option of a paging system controller transmitting address or receiver identity codes (RICs) in an order of increasing or decreasing numerical significance and if a pager which has been powered-
30 up for its predesignated frame notes from the first few bits of an address being received that it follows after its own address in the ordered sequence and

therefore there is not a call or message for itself, the receiver section of the pager is powered down before the end of the frame in order to save power.

WO99/25051 discloses a method of, and communications system for, battery economising in a telemetry system having remotely located terminal units, each unit including a radio receiver having a radio identity code consisting of M bits and a transmitter. A base station transmits a wake-up message consisting at least two repetitions of a wake-up sequence, the wake-up sequence comprising N concatenated parts, where N is an integer. Each of the N parts includes a sync code word and a different fraction M/N of bits of a radio identity code. The radio receiver in each terminal unit is energised intermittently in order to detect carrier and at least one of the N parts. In response to detecting the at least one of the N parts, the radio receiver remains energised and analyses at least the detected one of the N parts. If the received bits of the radio identity code do not correspond to the corresponding bits of the radio receiver's radio identity code, the radio receiver reverts to an intermittent energisation. If the complete radio identity code is detected the receiver remains energised to receive a message appended to the transmitted radio identity code.

Whilst all these known techniques enhance battery economising, there is a continuing desire to reduce demands for power by the radio receiver in order to extend the life of a battery thereby ensuring longer useful operating lives of the terminal units and ensure a prompt response can be given when required.

An object of the present invention is to facilitate power saving in communications apparatus.

According to one aspect of the present invention there is provided a method of operating a receiver, comprising energising the receiver, detecting the presence of a carrier signal, de-energising the receiver if the carrier signal is not detected, maintaining energisation of the receiver if the carrier signal is detected, detecting if the received signal is decodable, de-energising the

receiver if the signal is not decodable and if it is decodable, decoding the signal.

According to a second aspect of the present invention there is provided a communications system comprising a primary station having a transmitter for transmitting a signal and at least one secondary station having a receiver for receiving signals from the primary station, the receiver comprising signal receiving means, means for detecting the presence of a received signal, means for detecting the quality of the received signal and power control means for de-energising the receiver if the presence of a signal is not detected or the quality of the signal is unacceptable.

According to a third aspect of the present invention there is provided a receiver comprising signal receiving means, means for detecting the presence of a received signal, means for detecting the quality of the received signal and power control means for de-energising the receiver if the presence of a signal is not detected or the quality of the signal is unacceptable.

In an embodiment of the method in accordance with the present invention, each time a receiver is powered-up it uses a radio signal strength indication (RSSI) circuit to decide whether there is a signal present. If there is no signal, the receiver can be powered-down immediately without waiting for the expiry of a radio channel sampling period. Alternatively, if signal is detected the receiver remains energised and a check is made to see if not only is the signal present but also it is capable of being demodulated. The value of this second check, which is a quality check, is that if the detected signal is due to interference from say an adjacent channel, noise or another signal source, then there is no requirement to decode it and the receiver can be de-energised thus saving power. If the signal can be demodulated then the receiver decodes it.

The signal quality measure can also be used to filter out other signals within a communications system, especially signals on the same carrier but having different data rates.

The present invention will now be described, by way of example, with reference to the accompanying drawings, wherein:

Figure 1 is a diagrammatic view of a simplified embodiment of an automatic water metering system,

5 Figure 2 is a block schematic diagram of a consumer unit including a telemetry module,

Figure 3 is a flow chart of an implementation of the method in accordance with the present invention, and

Figure 4 is a table showing the different average receiver on times in
10 milliseconds (ms) for examples in which only the RSSI is measured (single stage carrier detection SSCD) and in which the RSSI and signal quality are determined (two stage carrier detection TSCD).

In the drawings the same reference numerals have been used to indicate corresponding features.

15

Referring to Figure 1, the simplified embodiment of the automatic water metering system comprises a plurality of consumer units CU1, CU2, CU3 attached to water conduits supplying a domestic premises. Each of the consumer units CU1 to CU3 comprises a metering unit 10 operatively coupled
20 to a microprocessor 12 and a transceiver 14 having an antenna 16 which may be incorporated into or comprise a cover for a boundary box set into the ground and containing the consumer unit CU1 to CU3.

The consumer units CU1 to CU3 can be interrogated remotely by in range network interrogation units (NIU) NIU1, NIU2 which relay meter reading
25 information by way of land lines 18, such as the PSTN, or further radio links (not shown) to a management interface unit MIU, which amongst other tasks controls the operation of the metering system and the billing of customers. Additionally the consumer units CU1 to CU3 may be interrogated remotely by portable NIUs (not shown) which store the meter reading information for later
30 transfer to the master interface unit MIU.

In Figure 1, each of the NIUs, NIU1 and NIU2, covers a respective plurality of meters in a particular geographic area. In order to be able to do

this, each of the NIUs is mounted in an elevated position on say a dedicated mast or a lamppost. Each of the NIUs comprises a controller 20 for controlling the operation of a transceiver 22 which may be similar to the transceiver 14 of the consumer unit, the storage of meter information in a store 24 and the
5 relaying of the stored meter information by way of a modem 26.

The master interface unit MIU has a controller comprising a large computer 30 which is coupled to a modem 32 which enables communication to be effected by way of the land lines 18.

The consumer unit CU shown in Figure 2 comprises a metering unit 10
10 and a telemetry module TM. The telemetry module TM comprises a radio receiver 34 and a radio transmitter 36 coupled to a common antenna 16. The radio receiver 34 may be of any suitable design, for example zero IF or superheterodyne. An output 38 of the receiver 34 is coupled to a demodulator 40 which in turn is coupled to a decoder 42. The decoder 42 is coupled to the
15 microprocessor 12.

An encoder 44 has an input 46 coupled to the microprocessor 12 and an output coupled to the radio transmitter 36.

A received signal strength indication (RSSI) circuit 48 is coupled to the radio receiver 34 for detecting the presence of a received signal. The circuit
20 48 has an output coupled to the microprocessor 12.

A signal quality measuring circuit 50 is coupled to the demodulator 40 for determining the quality of the recovered signal. The circuit 50 is coupled to an input of the microprocessor 12.

The microprocessor 12 operates in accordance with program software
25 store on a ROM 52. A power supply 54 for the telemetry module TM is connected to the microprocessor 12. A power control line 56 couples an output of the microprocessor 12 to a power control input 58 of the receiver 34.

In operation the microprocessor 12 will cause the radio receiver 34 to be energised and de-energised in accordance with the protocol software
30 stored in the ROM 52. However the control of power to the radio receiver 34 can be modified to enhance battery saving by the RSSI circuit 48 monitoring for the presence of a signal whenever the radio receiver is energised in

accordance with the protocol being followed. If no carrier signal within the channel is detected, then the microprocessor 12 causes the radio receiver 34 to be de-energised. However if a carrier signal is detected, the signal quality measuring circuit 50 checks the reliability of the demodulated data signals. If the signal quality is acceptable, the microprocessor 12 causes the radio receiver 34 to remain energised, but if the signal quality is unacceptable, it is de-energised.

The signal quality measuring circuit 50 provides a number of beneficial features which are additional to the RSSI circuit 48. The RSSI circuit 48 only detects the carrier for a short time and as a result may have a relatively high false alarm rate while avoiding false dismissals. In contrast the circuit 50 measures the ability to demodulate received data signal rather than just the power present in the channel. This means that the circuit 50 is robust to interfering signals whether noise or the like or modulated (if the interferer is using a different modulation scheme). Additionally the signal quality measure can be used to filter out other signals within the system that are at an unwanted data rate.

Figure 3 is a flow chart summarising the operations which have been described. Block 60 denotes the receiver 34 being de-energised. Block 62 denotes the microprocessor 12 switching-on the receiver 34. Block 64 denotes the RSSI circuit 48 checking for a carrier signal. Block 66 denotes checking if carrier signal has been detected. If the answer is no (N) then the flow chart proceeds to block 68 which denotes the receiver 34 being switched-off. Alternatively if the answer is yes (Y), the flow chart proceeds to block 70 which denotes the circuit 50 checking for signal quality. Block 72 denotes checking if the signal is of an acceptable quality. If the answer is no (N), the flow chart reverts to the block 68, but if the answer is yes (Y), the flow chart proceeds to the block 74 which denotes the signal being decoded.

Referring to the table shown in Figure 4 the rows 80 to 84 are three examples single stage carrier detection (SSCD) in which RSSI alone is measured and row 86 is an example of two stage carrier detection (TSCD) in which both RSSI and signal quality are measured.

The columns represent the following:

CDT	Carrier Detect Time in ms
CDFR	Carrier Detect False Rate
SQT	Signal Quality Time in ms
SQFR	Signal Quality False Rate
TFT	Total False Rate
AROT	Average Receiver On Time in ms.

10

The table shows the average length of time that the receiver 34 is powered up when it looks at an empty channel (it is assumed that if a carrier signal is falsely detected then the receiver will need to be powered up for a further 50 ms before the decoder 42 can terminate due to a lack of synchronisation). Comparing the three examples of checking for RSSI only with different length carrier detection times (rows 80, 82, 84) with checking for RSSI and quality in a two stage process (row 86), it will be noted that the two stage process gives the shortest average receiver on time (AROT) and hence the greatest battery saving.

20 In the present specification and claims the word "a" or "an" preceding an element does not exclude the presence of a plurality of such elements. Further, the word "comprising" does not exclude the presence of other elements or steps than those listed.

From reading the present disclosure, other modifications will be apparent to persons skilled in the art. Such modifications may involve other features which are already known in the design, manufacture and use of communication and telemetry systems and components therefor and which may be used instead of or in addition to features already described herein. Although claims have been formulated in this application to particular combinations of features, it should be understood that the scope of the disclosure of the present application also includes any novel feature or any novel combination of features disclosed herein either explicitly or implicitly or

30

any generalisation thereof, whether or not it relates to the same invention as presently claimed in any claim and whether or not it mitigates any or all of the same technical problems as does the present invention. The applicants hereby give notice that new claims may be formulated to such features and/or
5 combinations of such features during the prosecution of the present application or of any further application derived therefrom.

CLAIMS

1. A method of operating a receiver, comprising energising the receiver, detecting the presence of a carrier signal, de-energising the receiver
5 if the carrier signal is not detected, maintaining energisation of the receiver if the carrier signal is detected, detecting if the received signal is decodable, de-energising the receiver if the signal is not decodable and if it is decodable, decoding the signal.

10 2. A method as claimed in claim 1, characterised by measuring the received signal strength indication(RSSI) as a means for detecting the presence of the carrier signal.

3 A method as claimed in claim 1 or 2, characterised by measuring
15 signal quality as a measure for determining if a signal is decodable.

4. A communications system comprising a primary station having a transmitter for transmitting a signal and at least one secondary station having a receiver for receiving signals from the primary station, the receiver comprising
20 signal receiving means, means for detecting the presence of a received signal, means for detecting the quality of the received signal and power control means for de-energising the receiver if the presence of a signal is not detected or the quality of the signal is unacceptable.

25 5. A system as claimed in claim 4, characterised in that means for determining the received signal strength indication(RSSI) is coupled to the signal receiving means.

6. A receiver comprising signal receiving means, means for
30 detecting the presence of a received signal, means for detecting the quality of the received signal and power control means for de-energising the receiver if

the presence of a signal is not detected or the quality of the signal is unacceptable.

5 7. A receiver as claimed in claim 6, characterised in that means for determining the received signal strength indication(RSSI) is coupled to the signal receiving means.

10 8. A method of operating a receiver, substantially as hereinbefore described with reference to and as shown in the accompanying drawings.

 9. A communications system constructed and arranged to operate substantially as hereinbefore described with reference to and as shown in the accompanying drawings.

15 10. A receiver constructed and arranged to operate substantially as hereinbefore described with reference to and as shown in the accompanying drawings.

Abstract

BATTERY ECONOMISING IN A COMMUNICATIONS SYSTEM

5 In communications systems such as telemetry systems in which a receiver (34) is periodically energised to receive transmissions from a central station, the receiver includes power control means (12) for controlling the energisation of the receiver, a circuit (48) for detecting the presence of a carrier, which circuit (48) causes the power control means to de-energise the
10 receiver (34) in the event of carrier not being detected, and a signal quality measuring stage (50) for determining if the demodulated signal is decodable, the stage (50) causing the power control means to de-energise the receiver (34) in the event of the signal quality not being acceptable.

15 (Figure 2)

THIS PAGE BLANK (USPTO)




FIG. 1

THIS PAGE BLANK (USPTO)

2/4




Fig. 2.

THIS PAGE BLANK (USPTO)




Fig. 3

THIS PAGE BLANK (USPTO)

4/4

	CDT (ms)	CDFR	SQT (ms)	SQFR	TFR	AROT (ms)
SSCD 80	20	0.01	n/a	n/a	0.01	$20 + (0.01 \times 50) = 20.5$
SSCD 82	10	0.1	n/a	n/a	0.1	$10 + (0.1 \times 50) = 15$
SSCD 84	5	0.25	n/a	n/a	0.25	$5 + (0.25 \times 50) = 17.5$
TSCD 86	10	0.1	20	0.01	0.001	$10 + (0.1 \times 20) + (0.001 \times 50) = 12.0$

Fig. 4

THIS PAGE BLANK (USPTO)